

# Ames Engineering Profiler

Software Version 5.5.1.78  
SERIAL # 622108  
MODEL # Model\_6200

Company = Duit Construction  
Operator = Wayne Stanton  
Certification # = 2815  
Certification date = 00041548  
District =  
Route # = 2  
Pavement # = Cert  
Pass # = Default

## FILE

C:\JOBS\Odot Cert 12-8-16 L2.adf

## CALPRO SETTINGS

Band placement = Linear regression  
Band positioning = Off-set  
Band width(in.) = 0.000  
Min. scallop width(ft.) = 2.00  
Min. scallop height(in.) = 0.030  
Scallop rounding(in.) = 0.01  
Count scallops once = True  
Butterworth filter(ft.) = 4.00

## BUMP SETTINGS

Bump Height(in.) = 0.60  
Bump Width(ft.) = 25.00  
Bump Detection = On  
Dip Detection = Off

## ANALYSIS SETTINGS

Low pass Filter(ft.) = 0.00  
High pass Filter(ft.) = 0.00  
Reduction Length(ft.) = 528  
Horizontal Scale = 600 To 1  
Vertical Scale = 1 To 1  
Paper Factor = 1.800

## SENSOR SETTINGS

Sample rate = 12 samples/ft  
Collection Speed(mph) = 8.34  
Horizontal Cal. Divisor = 32  
Horizontal Calibration = 319.939  
Pre\Post Run Length = 300.00 ft  
Autostart offset (in.) 0.000  
ODS2 offset (in.) 0.000

## SENSOR 1 FILTERS

Collection Filter (ft.) = 256.32  
Analog filter = 0.30 rad.  
Anti-Aliasing Filter = 0 Hertz

--Collection Time and Date--

Time: 11:16:59 Date: 12-08-2016

--Printed Time and Date--

Time: 11:21:44 Date: 12-08-2016