

Ames Engineering Profiler

Software Version 6.0.4.126

SERIAL # 620216

MODEL # Model_6200

Company = Gary A Crain Inc
Operator = David Collins
Certification # = 3356
Certification date =
Project =
Job = Certify
County = Tulsa
Division =
Resident =
Highway = Tulsa Raceway Park
Lane = East
Lane Location = Driver Wheel Path
Pass = 1 Final
Comments =

FILE

C:\Jobs\Allen\Dondlinger\Certfy 1.ard

CALPRO SETTINGS

Band placement = Linear regression
Band positioning = Off-set
Band width(in.) = 0.000
Min. scallop width(ft.) = 2.00
Min. scallop height(in.) = 0.030
Scallop rounding(in.) = 0.01
Count scallops once = True
Butterworth filter(ft.) = 2.00

BUMP SETTINGS

Bump Height(in.) = 0.60
Bump Width(ft.) = 25.00
Bump Detection = On
Dip Detection = Off

ANALYSIS SETTINGS

Low pass Filter(ft.) = 0.00
High pass Filter(ft.) = 300.00
Reduction Length(ft.) = 528
Horizontal Scale = 300 To 1
Vertical Scale = 1 To 1
Paper Factor = 1.800

SENSOR SETTINGS

Sample rate = 12 samples/ft
Collection Speed(mph) = 10.14
Horizontal Cal. Divisor = 21
Horizontal Calibration = 318.023
Pre\Post Run Length = 0.00 ft

LEFT SENSOR FILTERS

Collection Filter (ft.) = 937.18
Analog filter = 0.10 rad.
Anti-Aliasing Filter = 0 Hertz

--Collection Time and Date--

Time: 11:20:14 Date: 12-08-2016