

Ames Engineering Profiler

Software Version 5.5.1.79
SERIAL # 622207
MODEL # Model_6000

Company = J R Sand
Operator = DeHoyos
Certification # =
Certification date = 00022616
District =
Route # = track 2
Pavement # = cal 2017
Pass # = Default

FILE

C:\Jobs\Dewey\dewey east bound driving6.
adf

CALPRO SETTINGS

Band placement = Linear regression
Band positioning = Off-set
Band width(in.) = 0.000
Min. scallop width(ft.) = 2.00
Min. scallop height(in.) = 0.030
Scallop rounding(in.) = 0.01
Count scallops once = True
Butterworth filter(ft.) = 3.00

BUMP SETTINGS

Bump Height(in.) = 0.60
Bump Width(ft.) = 25.00
Bump Detection = On
Dip Detection = Off

ANALYSIS SETTINGS

Low pass Filter(ft.) = 0.00
High pass Filter(ft.) = 0.00
Reduction Length(ft.) = 528
Horizontal Scale = 300 To 1
Vertical Scale = 1 To 1
Paper Factor = 1.800

SENSOR SETTINGS

Sample rate = 12 samples/ft
Collection Speed(mph) = 5.75
Horizontal Cal. Divisor = 21
Horizontal Calibration = 322.835
Pre\Post Run Length = 300.00 ft
Autostart offset (in.) 0.000
ODS2 offset (in.) 0.000

SENSOR 1 FILTERS

Collection Filter (ft.) = 176.61
Analog filter = 0.30 rad.
Anti-Aliasing Filter = 24 Hertz

--Collection Time and Date--

Time: 10:02:35 Date: 10-25-2017

--Printed Time and Date--

Time: 10:04:48 Date: 10-25-2017