

Ames Engineering Profiler

Software Version 5.5.1.79
SERIAL # 622207
MODEL # Model_6000

Company = J R Sand
Operator = DeHoyos
Certification # =
Certification date = 00022616
Project = 6
Job =
County =
Division = 6
Resident =
Highway = trace 2
Lane = 1
Lane Location = trace 2
Pass = Default
Comments = Default

FILE

C:\Jobs\2016 ok cal\odot cal2.adf

CALPRO SETTINGS

Band placement = Linear regression
Band positioning = Off-set
Band width(in.) = 0.000
Min. scallop width(ft.) = 2.00
Min. scallop height(in.) = 0.030
Scallop rounding(in.) = 0.01
Count scallops once = True
Butterworth filter(ft.) = 3.00

BUMP SETTINGS

Bump Height(in.) = 0.60
Bump Width(ft.) = 25.00
Bump Detection = On
Dip Detection = Off

ANALYSIS SETTINGS

Low pass Filter(ft.) = 0.00
High pass Filter(ft.) = 0.00
Reduction Length(ft.) = 528
Horizontal Scale = 300 To 1
Vertical Scale = 1 To 1
Paper Factor = 1.800

SENSOR SETTINGS

Sample rate = 12 samples/ft
Collection Speed(mph) = 7.80
Horizontal Cal. Divisor = 21
Horizontal Calibration = 322.159
Pre\Post Run Length = 300.00 ft
Autostart offset (in.) 0.000
ODS2 offset (in.) 0.000

SENSOR 1 FILTERS

Collection Filter (ft.) = 239.47
Analog filter = 0.30 rad.
Anti-Aliasing Filter = 24 Hertz

--Collection Time and Date--

Time: 11:32:21 Date: 12-08-2016